



25 MAXIMUM STONE & ADHESIVE THICKNESS

INDICATIVE PARTITION
OR WALL LINING

STRUCTURAL OPENING = 'X' DIMENSION + 31

OVERALL FRAME WIDTH = 'X' DIMENSION + 26

CLEAR OPENING = 'X' DIMENSION - 115

TYPICAL
FIXINGS BY
OTHERS

TEARDROP GASKET]

HEAVY DUTY BEARING HINGE

HIGH SECURITY 3 POINT LOCK [3HS]

FIRE BOARD AS TILE BACKER

3 MINIMUM GROUT GAP

STONE BY OTHERS

3 MINIMUM GROUT GAP

STONE ADHESIVE BY OTHERS

'X' DIMENSION

CHAMFER REQUIRED ON STONE
TO ALLOW FREE OPERATION OF DOOR

PROFABACCESS

PROFAB ACCESS Ltd
UNIT 52 FOURWAYS
CARYLON ROAD INDUSTRIAL ESTATE
ATHERSTONE
WARWICKSHIRE
CV9 1LH
TEL: 01827 718222 FAX: 01827 721092
HTTP://WWW.PROFABACCESS.COM
THIS DRAWING IS THE PROPERTY OF PROFAB ACCESS Ltd. AND MAY NOT BE
COPIED OR REPRODUCED IN WHOLE OR IN PART WITHOUT THE WRITTEN CONSENT
OF PROFAB ACCESS Ltd.

TOLERANCES UNLESS OTHERWISE STATED
MACHINING: ± 0.1 mm
SHEET METAL: ± 0.2 mm
ALL DIMS. IN mm DWG. NOT FOR DXF
PLEASE REMOVE TAGS & SHARP EDGES
DO NOT SCALE

FABRICATION DRAWING DETAILS
PART DESCRIPTION:
GENERAL ASSEMBLY ('X' CROSS-SECTION)
PRODUCT CODE/SPECIFICATION:
**PROFAB 2 HOUR FIRE RATED ACCESS PANEL
8000-2FR-TF-TD-3HS-SD**

FABRICATION DRAWING NO:
PACX-82T-1TF-3S100
ISSUE REF: **4-SW-1108**
DRAWN BY: **A STONE**
DATE: **02/11/2007**
MATERIAL GAUGE & TYPE:
N/A
PRODUCT FINISH:
SEE ROUTE CARD



25 MAXIMUM STONE & ADHESIVE THICKNESS

INDICATIVE PARTITION
OR WALL LINING

STRUCTURAL OPENING = 'Y' DIMENSION + 14

OVERALL FRAME HEIGHT = 'Y' DIMENSION + 9

CLEAR OPENING = 'Y' DIMENSION - 56

TEARDROP GASKET]

TYPICAL
FXINGS BY
OTHERS

HIGH SECURITY 3 POINT LOCK [3HS]

FIRE BOARD AS TILE BACKER

3 MINIMUM GROUT GAP

STONE BY OTHERS

STONE ADHESIVE BY OTHERS

'Y' DIMENSION

PROFABACCESS

PROFAB ACCESS Ltd
UNIT 52 FOURWAYS
CARYLON ROAD INDUSTRIAL ESTATE
ATHERSTONE
WARWICKSHIRE
CV9 1LH

TEL: 01827 718222 FAX: 01827 721092
HTTP://WWW.PROFABACCESS.COM

THIS DRAWING IS THE PROPERTY OF PROFAB ACCESS Ltd. AND MAY NOT BE
COPIED OR REPRODUCED IN WHOLE OR IN PART WITHOUT THE WRITTEN CONSENT
OF PROFAB ACCESS Ltd.

TOLERANCES UNLESS OTHERWISE STATED

MACHINING:

\$"S\$8]a g'1 - S"%S
S"s'8]a g'1 - S"%S
Ch Yfk lgY'1 - S") S

SHEET METAL:

: c Xlb['1 - S"&S
5b(i Uf'1 - S"%S
Ch Yfk lgY'1 - S") S

ALL DIMS. IN mm DWG. NOT FOR DXF
PLEASE REMOVE TAGS & SHARP EDGES

DO NOT SCALE

FABRICATION DRAWING DETAILS

PART DESCRIPTION:

GENERAL ASSEMBLY ('Y' CROSS-SECTION)

PRODUCT CODE/SPECIFICATION:

**PROFAB 2 HOUR FIRE RATED ACCESS PANEL
8000-2FR-TF-TD-3HS-SD**

FABRICATION DRAWING NO:

PACY-82T-1TF-3S100

ISSUE REF: **4-SW-1108**

DRAWN BY: **A STONE**

DATE: **02/11/2007**

MATERIAL GAUGE & TYPE:

N/A

PRODUCT FINISH:

SEE ROUTE CARD



STRUCTURAL OPENING 'Y' + 14

OUTSIDE FRAME

DOOR HEIGHT = 'Y' DIMENSION

`X` DIMENSION

OUTSIDE FRAME

STRUCTURAL OPENING 'X' + 31

3-POINT LOCK
ACCESS HOLE

3mm NOMINAL GAP
BETWEEN STONE FACING

3-POINT
EUROPROFILE
LOCK
& KEY ISOMETRIC

PROFABACCESS



PROFAB ACCESS Ltd
UNIT 52 FOURWAYS
CARYLON ROAD INDUSTRIAL ESTATE
ATHERSTONE
WARWICKSHIRE
CV9 1LH

TEL: 01827 718222 FAX: 01827 721092
HTTP://WWW.PROFABACCESS.COM

THIS DRAWING IS THE PROPERTY OF PROFAB ACCESS Ltd. AND MAY NOT BE
COPIED OR REPRODUCED IN WHOLE OR IN PART WITHOUT THE WRITTEN CONSENT
OF PROFAB ACCESS Ltd.

TOLERANCES UNLESS OTHERWISE STATED

MACHINING:

\$"\$\$'8]a g'1' - \$"%\$

\$"s'8]a g'1' - \$"&

Ch Yfk lgY'1' - \$"' s

SHEET METAL:

: c'Xlb['1' - \$"&\$

5b[i'Uf'1' - \$"& s

Ch Yfk lgY'1' - \$"' s

ALL DIMS. IN mm DWG. NOT FOR DXF

PLEASE REMOVE TAGS & SHARP EDGES

DO NOT SCALE

FABRICATION DRAWING DETAILS

PART DESCRIPTION:

GENERAL ASSEMBLY (ELEVATION)

PRODUCT CODE/SPECIFICATION:

**PROFAB 2 HOUR FIRE RATED ACCESS PANEL
8000-2FR-TF-TD-3HS-SD**

FABRICATION DRAWING NO:

PACE-82T-1TF-3S100

ISSUE REF: **4-SW-1108**

DRAWN BY: **A STONE**

DATE: **02/11/2007**

MATERIAL GAUGE & TYPE:

N/A

PRODUCT FINISH:

SEE ROUTE CARD