



25 MAXIMUM STONE & ADHESIVE THICKNESS

STRUCTURAL OPENING = 'X' DIMENSION + 33

'X' DIMENSION + 28

CLEAR OPENING = 'X' DIMENSION - 115

TYPICAL
FIXINGS BY
OTHERS

HEAVY DUTY BEARING HINGE

3 POINT LOCK [3PL]

TEARDROP GASKET

MOISTURE RESISTANT BOARD AS TILE BACKER

3 MINIMUM GROUT GAP

STONE BY OTHERS

3mm MINIMUM GROUT GAP

STONE ADHESIVE BY OTHERS

'X' DIMENSION

CHAMFER REQUIRED ON STONE
TO ALLOW FREE OPERATION OF DOOR

PROFABACCESS

PROFAB ACCESS Ltd
UNIT 52 FOURWAYS
CARYLON ROAD INDUSTRIAL ESTATE
ATHERSTONE
WARWICKSHIRE
CV9 1LH

TEL: 01827 718222 FAX: 01827 721092
HTTP://WWW.PROFABACCESS.COM

THIS DRAWING IS THE PROPERTY OF PROFAB ACCESS Ltd. AND MAY NOT BE
COPIED OR REPRODUCED IN WHOLE OR IN PART WITHOUT THE WRITTEN CONSENT
OF PROFAB ACCESS Ltd.

TOLERANCES UNLESS OTHERWISE STATED
MACHINING: SHEET METAL:
S"SS"8ja g'1 - S"%S : c"Xlb["1 - S"&S
S"SS"8ja g'1 - S"8 5b[1 "U"1 - S"8 s
ChYrk lgY'1 - S") S ChYrk lgY'1 - S") S

ALL DIMS. IN mm DWG. NOT FOR DXF
PLEASE REMOVE TAGS & SHARP EDGES

DO NOT SCALE

FABRICATION DRAWING DETAILS

PART DESCRIPTION:

GENERAL ASSEMBLY ('X' CROSS-SECTION)

PRODUCT CODE/SPECIFICATION:

**PROFAB NON FIRE RATED ACCESS PANEL
8000/NFR/HF**

FABRICATION DRAWING NO:

PACX-80T-1HF-3P100

ISSUE REF: **A STONE**

DRAWN BY: **A STONE**

DATE: **02/11/2007**

MATERIAL GAUGE & TYPE:

N/A

PRODUCT FINISH:

SEE ROUTE CARD