



25 MAXIMUM STONE & ADHESIVE THICKNESS

STRUCTURAL OPENING = 'Y' DIMENSION + 18

'Y' DIMENSION + 13

CLEAR OPENING = 'Y' DIMENSION - 50

TEARDROP GASKET

3 POINT LOCK [3PL]

TYPICAL
FIXINGS BY
OTHERS

MOISTURE RESISTANT BOARD AS TILE BACKER

3 MINIMUM GROUT GAP

STONE BY OTHERS

STONE ADHESIVE BY OTHERS

'Y' DIMENSION

PROFABACCESS

PROFAB ACCESS Ltd
UNIT 52 FOURWAYS
CARYLON ROAD INDUSTRIAL ESTATE
ATHERSTONE
WARWICKSHIRE
CV9 1LH

TEL: 01827 718222 FAX: 01827 721092
HTTP://WWW.PROFABACCESS.COM

THIS DRAWING IS THE PROPERTY OF PROFAB ACCESS Ltd. AND MAY NOT BE
COPIED OR REPRODUCED IN WHOLE OR IN PART WITHOUT THE WRITTEN CONSENT
OF PROFAB ACCESS Ltd.

TOLERANCES UNLESS OTHERWISE STATED

MACHINING:

S"SS"8ja g"1" - S"%S
S"SS"8ja g"1" - S"8
ChYrk lgY"1" - S")S

SHEET METAL:

:cXlb["1" - S"&S
5bl1 "U"1" - S"8
ChYrk lgY"1" - S")S

ALL DIMS. IN mm DWG. NOT FOR DXF

PLEASE REMOVE TAGS & SHARP EDGES

DO NOT SCALE

FABRICATION DRAWING DETAILS

PART DESCRIPTION:

GENERAL ASSEMBLY ('Y' CROSS-SECTION)

PRODUCT CODE/SPECIFICATION:

**PROFAB NON FIRE RATED ACCESS PANEL
8000/NFR/HF**

FABRICATION DRAWING NO:

PACY-80T-1TF-3P100

ISSUE REF: **A STONE**

DRAWN BY: **A STONE**

DATE: **02/11/2007**

MATERIAL GAUGE & TYPE:

N/A

PRODUCT FINISH:

SEE ROUTE CARD